PIPE INLET BARRIER



SECTION A-A



PLAN VIEW

NOTES FOR PIPE INLET BARRIER:

1. PLACE PIPE INLET BARRIERS AT LOCATIONS SHOWN ON THE PLANS OR AS DIRECTED BY THE ENGINEER.
2. MAINTAIN A PROPERLY FUNCTIONING SEDIMENT BARRIER THROUGHOUT CONSTRUCTION.
3. REMOVE SEDIMENT AS IT ACCUMULATES AND PLACE IT IN A STABLE AREA APPROVED BY THE ENGINEER.
4. WHEN SURROUNDING AREAS HAVE BEEN SEEDED AND MULCHED, REMOVE THE STONE BARRIER BY SPREADING THE STONE ALONG THE CUT DITCH.
5. AN 18" MINIMUM DIAMETER FIBER ROLL MAY BE USED AS A SUBSTITUTE FOR THE STONE BARRIER. STAKE AS SHOWN ON STD DRW EN 1.

CURB INLET BARRIER



SECTION B-B



PLAN VIEW

NOTES FOR CURB INLET BARRIER:

1. PLACE BUILDING BLOCKS, WIRE MESH AND STONE AS SHOWN AROUND THE CURB INLETS.
2. MAINTAIN A PROPERLY FUNCTIONING STONE BARRIER THROUGHOUT CONSTRUCTION OR UNTIL DISTURBED AREAS CONTRIBUTING TO THE INLET HAVE BEEN PAVED OR VEGETATED.
3. REMOVE SEDIMENT AS IT ACCUMULATES AND PLACE IT IN A STABLE AREA APPROVED BY THE ENGINEER.

REVISIONS

NO.	DATE	APPR.	REMARKS

UTAH DEPARTMENT OF TRANSPORTATION
STANDARD DRAWINGS FOR ROAD AND BRIDGE CONSTRUCTION
SALT LAKE CITY, UTAH

RECOMMENDED FOR APPROVAL — JAN.01.2008 DATE
CHAIRMAN STANDARDS COMMITTEE APPROVED — JAN.01.2008 DATE
DEPUTY DIRECTOR

TEMPORARY EROSION CONTROL (PIPE INLET AND CURB INLET BARRIERS)

STANDARD DRAWING TITLE

STD DWG
EN 5